

PROSPERO

Nitrogen/Air Gas Generator for GC

Reference : PROSPERO.[Flow rate]/0 (Without compressor)
PROSPERO.[Flow rate]/1 (With compressor)



Description.

The combined Nitrogen/Air delivers a continuous stream of High Purity Nitrogen gas (> 99.9995%) and grade purify Air with Hydrocarbon content (< 0.1 ppm), ideal for application such as GC-Carrier gas, GC-Make up and GC-FID.

The PROSPERO is available without or with integrated oil free air compressor using the **Energy Saving Technology mode (EST)**. It is extremely compact and quiet in operation.

The generator is controlled using the latest in color touch screen technology to display the process in real time, inlet / outlet pressure, N2 Flow and status of the system with remote access for diagnostic control.

Utilizing **Advanced technology PSA** of separating Nitrogen and O2 to produce high quality Nitrogen gas and activated alumina column to produced purify Air on demand 24/7.



UNIQUE AND INTELLIGENT OPERATOR INTERFACE WITH REMOTE ACCESS

Applications

- GC-Carrier gas
- GC-FID
- GC-FPD
- GC-Make up
- GC-NPD
- GC-TCD

Benefits & Savings

INCREASED LABORATORY EFFICIENCY

A constant, uninterrupted gas supply of guaranteed purity eliminates interruptions of analyses to change cylinders and reduces the amount of instrument re-calibrations required.

IMPROVED ECONOMY

Pure Nitrogen and Pure Air gas produced as standard.

IMPROVED SAFETY

Pure Nitrogen and Pure Air produced at low pressure and ambient temperature removes the need for high pressure cylinders.

SECURITY OF SUPPLY

Integral oil free air compressor as an option guarantees continuous gas supply, independent of in house compressed air supply.

SIMPLE INSTALLATION

Gas generators can be installed in the laboratory, on or under a bench, eliminating the need for long gas lines from cylinders secured elsewhere.

Standard Features

- Intelligent color touch screen to provide simple and user friendly management of all functions of the unit
- Fully regenerative PSA technology
- Without or with integral oil free air compressor
- Quiet thanks to the Soundproofed compressor box and anti-vibration features
- Option :
Oxygen sensor : Online N2 Purity monitoring capability
- Auto start
- Fast start-up purity < 60 min
- Audible alarm display and Visual maintenance indication with history log
- Outlet Nitrogen/Air flow indicator
- Energy Saving Technology (EST) :
- Switch off the compressor when gas supply is not required
- Allowing low energy consumption and increasing durability of the compressor
- Remote PC monitoring and diagnostic analysis via USB to interface the unit with customer's PC software (allow to carry out checks and maintenance effectively, only via a remote connection)
- Compact design
- Fit with wheels



MODELS	PROSPERO.1		PROSPERO.3	
Compressor	0 (Without)	1 (With)	0 (Without)	1 (With)
GENERALS INFORMATIONS				
Max Nitrogen Flow rate	1 L/min		3 L/min	
Max Pure Air Flow rate	1.5 L/min		3 L/min	
Max N2/Air pressure	6 bar (87 psi)			
Nitrogen purity	> 99.9995% (< 5 ppm O2)			
Pure Air purity	HCs < 0.1 ppm ; Air Dew Point < -55°C (-67°F)			
Particles	0.01 μ			
Inlet Air flow required @ 8 bar (116 psi) max	16 L/min	N/A	42 L/min	N/A
Min Inlet Air quality	ISO8573 - 1:2010 1.4.1	N/A	ISO8573 - 1:2010 1.4.1	N/A
Touch screen	Touch screen (operating parameters, system status, alarms and maintenance)			
Max Relative Humidity	80% RH @ 25°C (77°F)			
Temperature range	From 5 - 25°C (41 - 77°F)			
Max Altitude	3000 Meters			
Noise level @ 1M	25 dB (A)	50 dB (A)	25 dB (A)	52 dB (A)
Dimensions (W x H x D)	47.5 x 66.2 x 65 cm (18.7" x 26" x 25,6")		47.5 x 66.2 x 79 cm (18.7" x 26" x 31")	
Weight (kg/lbs)	57 / 125	64 / 141	95 / 209	107 / 236
Power consumption	150 VA	350 VA	150 VA	850 VA
Electrical supply	220 - 240 V ac / 1 ph / 50 - 60 Hz			
	110 - 120 V ac / 1 ph / 50 - 60 Hz			
Fuse	10A			
CONNECTIONS				
Nitrogen/Air outlet	G 1/4" (BSP) Female			
Air Inlet	G 1/4" (BSP) Female	N/A	G 1/4" (BSP) Female	N/A
COMMUNICATION				
USB/PC Control	In series			

Gold Service
— Satisfaction Guaranteed —

The products are guaranteed 24 months*. Beyond, your investment continues to be supported by our maintenance program **[Gold Service]**. Our world class technical assistance offers Programmed preventive maintenance to ensure optimal performance of your Gas generator F-DGSi and a priority intervention in case of failure.

*Year 2 of warranty subject to generator being serviced at end of the first year by a F-DGSi-approved agent in accordance with fixed annual maintenance schedule. For full terms and conditions, visit www.f-dgs.com

GS: TECNOLOGIA APLICADA 

Certified Product

